











NIMMSTA HS 50 TECHNOLOGY LEADER



KEY FEATURE	NIMMSTA HS 50
DISPLAY	✓
TOUCH DISPLAY 	✓
DISPLAY SIZE	1,54 INCH
WMS INTERACTION VIA TOUCH DISPLAY 	✓
SCAN TRIGGER 	TOUCH DISPLAY TRIGGER PAD (LEFT/RIGHT)
ERGONOMIC 	ADJUSTABLE TRIGGER POSITION FOR EVERY WORKER
MODULAR 	SCANNER + TRIGGER PAD + CUFF
WIRELESS COMMUNICATION	BLUETOOTH 5.0 LOW ENERGY CONNECTION
BARCODES	1D, 2D, POSTAL, DOT-CODE
SCAN PERFORMANCE	UP TO 4 SCANS/SEC
TRANSMISSION FEEDBACK	ACOUSTIC, OPTICAL, HAPTIC
TRANSMISSION RANGE (FREE FIELD)	UP TO 100M
EASY PAIRING	VIA QR-CODE
AUTO RECONNECT	✓
ONLINE CONFIGURATION TOOL	✓
CLIENT OPERATING SYSTEM	ANDROID, WINDOWS, iOS (iOS IN PROGRESS)
SOFTWARE INTEGRATION VIA CORE LIBRARY	✓
CENTRAL DEVICE MANAGEMENT AND CONFIGURATION 	✓
MEASUREMENTS (DEVICE) 	55x44x17mm, 45g
IP CLASS 	IP 65
SHOCK RESISTANCE (TUMBLES)	500 DROPS FORM 1M ON STEEL
BATTERY LIFE	UP TO 6.000 SCANS
CHARGING PROCEDURE 	INDUCTIVE
CHARGING STATION 	SINGLE MULTIPLE (UP TO TEN)